

MARKED-UP COPY OF AMENDED CLAIMS:

1. (Amended) A ~~partition-creating method~~ for creating a partition in a storage device, the method comprising:

limiting a size of ~~a the~~ partition to be created to a size of ~~m~~ to ~~n-th~~ power, wherein ~~m~~ and ~~n~~ are natural numbers; and

disposing the partition to be created at a position in the storage device that is aligned with the size of the partition.

2. (Amended) A ~~partition-creating method~~ for creating a partition in a storage device, the method comprising:

~~partition-creating request receiving processing of receiving~~ a request to create a partition having a requested size of ~~m~~ to ~~n-th~~ power ~~(requested size)~~, where ~~m~~ and ~~n~~ are natural numbers, and,

~~partition disposing processing of referring to a table recording containing disposition information of partitions in the storage device, and when~~

determining whether there is an empty region in the storage device having a size equal to the requested size based on the disposition information and, if so, disposing the partition in the that empty region,

~~when there is not an empty region having the size equal to the requested size, and if determining, based on the disposition information, whether there is an empty region having a size mk times as large as the requested size (where k is a natural number) when an empty region having the requested size does not exist, and, if so, continuing to divide by m the successively dividing that empty region of the size mk times till by m until the size of the divided empty region becomes equal to the requested size, and disposing the partition in the thus obtained divided region of a size equal to the requested size, where k is a natural number, or the storage device, and~~

~~when there is neither the region having the size equal to the requested size nor the region having the size of mk times the requested size, disposing the partition in a region where a~~

partition can be created, the region being a position that can be aligned with the requested size when there is neither a region having the requested size nor a region having mk times the requested size.

3. (Amended) The ~~partition creating method~~ according to claim 2,

~~wherein said partition creating request receiving processing comprises the step of receiving the request to create a partition includes receiving a request of creating to create a partition of an arbitrary size, and using adopting, as the requested size, a size of m to the n -th power, which size where n is at a minimum that meets the size of the received partition and is represented by a minimum n request.~~

4. (Amended) A ~~partition deleting method~~ of deleting a partition ~~that is created in a storage device and that~~ has a size of m to n -th power, where m and n are natural numbers, the method comprising ~~the steps of:~~

receiving information specifying a partition to be deleted;
and

referring to a table ~~recording~~ containing disposition information concerning the partition in the storage device, and when

determining whether a region before or after the partition to be deleted is an empty region, and if whether a region obtained by combining the empty region and the partition to be deleted can be aligned with a total size obtained by totaling a size of the empty region and a size of the partition to be deleted, and, if so, combining the empty region and a region having the partition deleted therefrom.

5. (Amended) A storage medium containing a computer program for causing a computer to execute actions comprising:

~~processing of receiving a request to create a partition having a size of m to n -th power, where m and n are natural numbers; and~~

~~processing of creating a the partition in a region on a storage device, where the partition of the received size can be created, the region being in a position that is aligned with the received size.~~

6. (Amended) A storage medium containing a computer program for causing a computer to execute actions comprising:

~~partition creating request receiving processing of receiving a request to create a partition having a requested size of m to n -th power (~~requested size~~), where m and n are natural numbers; and~~

~~partition disposing processing of referring to a table recording containing disposition information concerning a partition in a storage device, and when~~

~~determining whether there is an empty region in the storage device having a size equal to the requested size based on the disposition information and, if so, disposing the partition in the that empty region,~~

~~when there is not an empty region having the size equal to the requested size, and if determining, based on the disposition information, whether there is an empty region having a size mk times as large as the requested size (where k is a natural number) when an empty region having the requested size does not exist, and, if so, continuing to divide by m the successively dividing that empty region having the size mk times till by m until the size of the divided empty region becomes equal to the requested size, and disposing the partition in the thus obtained divided region of a size equal to the requested size, where k is a natural numberthe storage device, and~~

~~when there is neither the region having the size equal to the requested size nor the region having the size $2k$ times as large as the requested size, disposing the partition in a region where a partition can be created, the region being a position aligned with the requested size when there is neither a region~~

having the requested size nor a region having mk times the requested size.

7. (Amended) The ~~computer program~~ storage medium according to claim 6,

~~wherein said partition creating request receiving processing comprises the step of receiving the request to create a partition includes receiving a request of creating to create a partition of an arbitrary size, and using adopting, as the requested size, a size of m to the n -th power, which size where n is at a minimum that meets the size of the received partition and is represented by a minimum n request.~~

8. (Amended) A storage medium containing a computer program for causing a computer to execute ~~processing a process of deleting a partition that is created in a storage device and that~~ has a size of m to n -th power, where m and n are natural numbers, ~~the computer program being for causing the computer to execute process including:~~

~~processing of receiving information specifying a partition to be deleted; and~~

~~processing of referring to a table recording containing disposition information concerning the partition in the storage device, and when~~

~~determining whether a region before or after the partition to be deleted is an empty region, and if whether a region obtained by combining the empty region and the partition to be deleted can be aligned with a total size obtained by totaling a size of the empty region and a size of the partition to be deleted, and, if so, combining the empty region and the region having the partition deleted therefrom.~~

9. (Amended) An information processing apparatus, comprising:

means for receiving a request to create a partition having a size of m to n -th power, where m and n are natural numbers; and

means for creating the partition in a region on a storage device, ~~where the partition can be created by the received size,~~ the region being in a position that is aligned with the received size.

10. (Amended) An information processing apparatus, comprising:

~~partition creating request receiving~~ means for receiving a request to create a partition having a requested size of m to n -th power ~~(requested size)~~, where m and n are natural numbers; and

~~partition disposing~~ means for referring to a table recording containing disposition information concerning a partition partitions in a storage device, ~~when~~ for determining whether there is an empty region of in the storage device having a size equal to the requested size, and for disposing the partition in the that empty region, and

~~when there is not an empty region of the size equal to the requested size, and if~~ means for determining, based on the disposition information, whether there is an empty region having a size mk times as large as the requested size (where k is a natural number) when an empty region having the requested size does not exist, and if so, continuing to divide by m the for successively dividing that empty region having the size mk times till by m until the size of the divided empty region becomes equal to the requested size, and for disposing the partition in the thus obtained divided region having a size equal to the requested size, where k is a natural number of the storage device, and

~~when there is neither the region having the size equal to the requested size nor the region having the size $2k$ times as large as the requested size,~~ means for disposing the partition in a region where a partition can be created, the region being a position aligned with the requested size, when there is neither a region having the requested size nor a region having mk times as large as the requested size.

11. (Amended) The information processing apparatus according to claim 10,

~~—wherein said partition creating request receiving means~~
receives means for receiving a request is operable to receive a
request to create a partition of an arbitrary size, and ~~use to~~
adopt, as the requested size, a size of m to the n -th power,
~~which size where n is at a minimum that meets the size of the~~
~~received partition and is represented by a minimum n request.~~

12. (Amended) An information processing apparatus including
~~unit for deleting a partition that is created on in a storage~~
device and that has a size of m to n -th power, where m and n are
natural numbers, the apparatus comprising:

means for receiving information for specifying a partition
to be deleted; and

means for referring to a table ~~recording~~ containing
disposition information concerning the partition in the storage
device, and when a region before or after the partition to be
deleted is an empty region, and if a region obtained by combining
the empty region and the partition to be deleted is aligned with
a total size obtained by totaling a size of the empty region and
~~a size of the partition to be deleted, for combining the empty~~
region and the region having the partition deleted therefrom.

~~13. A computer readable storage medium recorded with the
computer program according to any one of claims 5 to 8.~~

14. (Amended) A storage device ~~having a plurality of~~
partitions ~~created therein, comprising:~~

a plurality of created partitions, and

a management region which manages a size and position of
each created partition,

~~—wherein said the management region having includes size~~
information and position information therein, the size
information ~~indicating~~ indicates that each created partition has
a size of m to the n -th power, wherein m and n are natural

numbers, and the position information ~~indicating~~ indicates that each created partition is disposed at a position aligned with the size of the partition.

~~15. A storage device having a partition,
—wherein the partition is created by a partition creating
method as defined in any one of Claims 1 to 3.~~

16. (Amended) A method ~~for comprising~~ recording data on a storage device,
—wherein the data manages a size and position of ~~a partition~~ created partitions on the storage device, ~~and the data includes~~ size information and position information, the size information ~~indicating~~ indicates that each created partition has a size of m to n -th power, ~~wherein m and n are natural numbers, and~~ the position information ~~indicating~~ indicates that each created partition is disposed at a position aligned with the size of the partition.

REMARKS

Applicant respectfully requests consideration and allowance of claims 1-12, 14, and 16-19 that are pending the above identified application. Applicant has cancelled claims 13 and 15, amended claims 1-12, 14, and 16, and added new claims 17-19. No new matter has been added by the claim amendments.

Applicant has requested that the Examiner review and approve the enclosed change to FIG. 4, marked in red on the attached copy of same. This change to FIG. 4 corrects for a typographical error. No new matter is added by the drawing change. Applicant submits herewith a formal drawing of FIG. 4 which includes the change in anticipation of the Examiner's approval.

Applicant has requested that the Examiner approve and enter the attached substitute specification under 37 C.F.R. § 1.125 and MPEP § 608.01(q). The changes to the specification, are believed to place the application in better form for U.S. practice. No new matter has been added by the substitute specification.

In light of the above, Applicant submits that the instant application is in condition for allowance. Early and favorable action is earnestly solicited. If, however, for any reason the Examiner does not believe such action can be taken, it is respectfully requested that he or she telephone Applicant's attorney at (908) 654-5000 in order to overcome any objections that he or she may have.

Application No. 10/033,157

If there are any additional charges in connection with this requested amendment, the Examiner is authorized to charge Applicant's Deposit Account No. 12-1095 therefor.

Respectfully submitted,


LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK, LLP

A handwritten signature in dark ink, appearing to read "Matthew B. Dernier", with a long horizontal flourish extending to the right.

MATTHEW B. DERNIER
Reg. No. 40,989

600 South Avenue West
Westfield, NJ 07090-1497
Telephone: (908) 654-5000
Facsimile: (908) 654-7866

344015_1.DOC



PARTITION CREATING METHOD AND DELETING METHOD

~~TECHNICAL FIELD~~ BACKGROUND OF THE INVENTION

[0001] The present invention relates to a management technology of a storage device, particularly to a technology of managing creation and deletion of a partition of a hard disk device.

~~BACKGROUND ART~~

[0002] In a storage device, particularly in a hard disk, the setting of partitions makes it possible to ~~use physically~~ physically use one hard disk as if it were separate hard disks. It is therefore an actual practice to divide a hard disk having a large capacity into a plurality of partitions, for facilitating management of the disk or enabling the booting up of a plurality of OSs by switching one OS to another. Further, the partitions are also used for the purpose of preventing a decrease in a processing speed, which is caused by an occurrence of so-called fragmentation, by reeording To this end, files to be frequently opened for reading and writing, and system files and the like to be altered to a less degree are recorded in separate partitions.

[0003] When a user conducts partition alteration, conventionally, the user ~~uses~~ employs a utility program or the like to manually add or delete partition(s). That is, when the user adds a partition, the user takes account of

a necessary partition size and a securable region ~~in~~on a hard disk to determine the position of partition to be created.

~~DISCLOSURE OF THE INVENTION~~

[0004] ~~Meanwhile, the~~ In practice, however, partition alteration has not been performed ~~so~~very frequently. The alteration has been limited, for example, to the case of adding a hard disk, the case of changing operation systems, and the like.

[0005] However, there are ~~generated demands~~ for adding and deleting a partition ~~as required thanks to~~ for enlargement of a hard disk capacity, diversification of operation systems, addressing a necessity to handle files having various properties.

[0006] In such a case, ~~when~~if the addition and deletion of the partitions are ~~disorderedly repeated~~ in a disorderly way, the hard disk is fragmented into minute partitions, which may lower the utilization efficiency of a hard disk device.

SUMMARY OF THE INVENTION

[0007] It is an object of the present invention to provide a technology for improving the utilization efficiency of a storage device.

[0008] For achieving the above ~~subject, a partition creating~~

and/or other objects, a method of creating a partition in
a storage device, provided by the present invention,
comprises limiting the size of a partition to be created to
a size of m to the n -th power where m and n are natural
numbers, and disposing the partition to be created in a
position aligned by the size of the partition.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Fig. 1 is a block diagram showing a ~~constitution~~
configuration of one embodiment of the partition management
system according to the present invention.

[0010] Fig. 2 is a view for explaining partitions as
divisional regions of a hard disk in this embodiment.

[0011] Fig. 3 is a view showing one example of a structure
of a partition management table-103.

[0012] Fig. 4 is a flowchart for explaining ~~processing in~~
a process for creating the partition.

[0013] ~~Fig. 5 is a view~~ Figs. 5A-5D are views for explaining
~~a processing an example in of a process for creating the~~
partition.

[0014] Fig. 6 is a view for explaining ~~processing in a~~
process for creating the partition in a final undefined
region.

[0015] Fig. 7 is a flowchart for explaining ~~processing in~~
a process for deleting the partition.

[0016] ~~Fig. 8 is a view~~ Figs. 8A-8G are views for explaining

~~a processing example in~~ examples of processes for deleting
the partition.

~~BEST MODE FOR EMBODYING THE INVENTION~~ DETAILED DESCRIPTION
OF THE INVENTION

[0017] Embodiments of the present invention will be explained in detail with reference to the drawings.

[0018] Fig. 1 is a block diagram showing a ~~constitution~~ configuration of one embodiment of a partition management system according to the present invention. In this drawing, a partition management system 100 includes an interface unit 101 for receiving a program under execution, a request for adding a partition and a request for deleting a partition from an operator or the like and sending results of processing the same back thereto. The partition management system 100 also includes a partition management execution unit 102 for executing addition and deletion of a partition in a mounted storage device and performing creation and renewal of a partition management table. ~~And~~ The partition management system 100 also includes a partition management table 103. In this embodiment, a hard disk 110, as one example of the storage device, is mounted in the partition management system 100.

[0019] ~~The partition management system 100~~ execution unit 102 includes: a central processing unit (CPU), a main storage device, a reading device for reading data from a

portable storage medium, such as a CD-ROM or DVD-ROM, an input device such as a keyboard, a mouse and a controller, a display device ~~such as a display~~, and an interface for controlling transmission and reception of data among the above-described constituent components. The partition management system 100 can be ~~constituted on~~ implemented using a generally configured information processing apparatus capable of internally or externally mounting the storage device, such as a hard disk, ~~—~~. The information processing apparatus may be, for example, a personal computer, a server computer or an entertainment apparatus. [0020] Further, a program for ~~allowing~~ commanding the information processing apparatus to execute the processing of the partition management system 100 can be included, for example, as part of utility software, a hard disk driver, a library for development, or the like. Such a program can be recorded in a storage medium, such as a CD-ROM and a DVD-ROM, and distributed to users. Alternatively, The program can be distributed ~~through~~ over a communication line.

[0021] In this embodiment, for specifying a sector as a unit of a recording region ~~in on~~ the hard disk, it is determined that a logical block address (LBA) starting from 0 is used. This address makes it possible to identify any sector on the hard disk. Naturally, the present invention is not limited thereto, and there may be employed a ~~constitution~~ configuration in which any sector on the hard disk is

specified by designating, for example, a cylinder number, a head number and a sector number. The logical block address will be referred to as a sector number for convenience.

[0022] Fig. 2 is a view for explaining partitions as divisional regions of the hard disk in this embodiment.

[0023] In the present invention, a partition created by the operator, the program under execution, or the like so that it permits reading/writing of data is referred to as a defined region (partition), ~~and~~ a storage region in which no partition is created yet or a partition created once is deleted is referred to as an undefined region. The above undefined region will be sometimes referred to as an undefined partition for convenience.

[0024] In this drawing, four regions (110a, 110b, 110c and 110d) are formed on the hard disk 110. Of these, the regions 110a and 110c are defined partitions that permit reading/writing of data. The region 110b, which is present between the regions 110a and 110c, is an undefined region. The region 110d, following which follows the region 110c, is an undefined region, which is assumed to continue to the end of the hard disk 110. That is, this drawing shows a state where the partition 110a and the partition 110c are created on the hard disk in an initial state.

[0025] Of the above undefined regions, an undefined region followed by a defined region or another undefined region like the region 110b is referred to as an "empty undefined

region." ~~and an~~ An undefined region that is the last region of the hard disk, like the region 110d, is referred to as a "final undefined region".

[0026] Each region has a header portion having a predetermined size ~~on a head thereof~~. Each header portion is to pre-record, for example, information to the effect that it is a head of the partition, a flag for identifying whether the partition (region) is already defined or undefined, and a size of the partition. The size of the partition can be represented, for example, by the number of sectors and the number of bytes. Alternatively, an ending sector number may be recorded to indirectly represent the size of the partition.

[0027] However, the information recorded in the header portion is not limited to the above-described ~~ones~~ information. For example, the information to the effect that the header is the head of the partition may be replaced with a leading sector number of the partition. Further, an identifier for identifying the partition, for example, a partition number may be recorded in the header portion. Furthermore, when the partition is, for example, undefined, the partition size may be set at 0 without using the above flag as the information for identifying whether the partition is already defined or undefined.

[0028] An operation of the partition management system 100 in this embodiment will now be explained ~~below~~ with

reference to Fig. 3. The operation of the partition management system 100 is divided into ~~processing a process~~ of creating the partition management table 103, ~~processing a process~~ of adding a partition, and ~~processing a process~~ of deleting the partition.

[0029] First, the ~~processing process~~ of creating the partition management table 103 will be explained.

[0030] The partition management table 103 is a table that is created on a the main storage device, or the like, by the partition management execution unit 102 for managing information concerning the partitions on the hard disk. It is understood that Fig. 3 is a view showing one example of structure of the partition management table 103.

[0031] In this drawing, the partition management table 103 has identifiers 1031, starting sector numbers 1032, sizes 1033 and statuses 1034.

[0032] The identifiers 1031 are used for identifying the partitions, and this example uses numbers in a ~~deseending~~ an ascending order. The statuses 1034 are information for identifying whether the respective regions are already defined or undefined.

[0033] The partition management execution unit 102 creates the partition management table 103 when the partition management system 100 is activated, when the hard disk device is mounted on the storage device, or the like.

[0034] Specifically, the partition management execution

unit 102 refers to the header portions recorded ~~in~~ on the hard disk 110, acquires the leading sectors, acquires the sizes and the information for identifying whether the region is defined or undefined with regard to each partition (including the undefined regions), and records the same in the partition management table 103.

[0035] The ~~above~~ partition management table 103 may be created on the hard disk, for example, at a managing region of the hard disk in advance. In this case, the partition management execution unit 102 can manage the partitions by referring to this region.

[0036] The ~~processing in process~~ for adding the partitions will be explained below.

[0037] In this embodiment, the size of the partition to be added is assumed to be 2 to the n-th power times as large as a base unit. The base unit has an arbitrary size, and can be determined to be ~~1~~ one sector (typically 512 bytes), ~~1~~ one cluster, ~~1~~ one kilobyte, ~~1~~ one megabyte, ~~100~~ one-hundred (100) megabytes, ~~1~~ one gigabyte and the like. However, this embodiment will be ~~explained~~ described on the assumption that the base unit is one sector.

[0038] The size of the ~~part~~ition to be added will be any one of 1, 2, 4, 8, 16, 32, ..., 1024, ... sectors, which are 2 to the n-th power times as large as one sector. ~~Where no particular confusion occurs~~ For simplicity, in the following explanation, sizes are represented without the

unit "sector". Further, the size of the partition to be added is not limited to the size that is 2 to the n-th power times as large, and can be a size that is any natural number to the n-th power times as large, for example, 3 to the n-th power, 4 to the n-th power times as large.

[0039] Even when a substantially necessary partition size is, for example, 3, therefore, the partition size which this system is requested to add is 4, which is 2 to the second power ($2^1 < 3 \leq 2^2$). Similarly, when 1000 is necessary, 1024 (2^{10}) becomes a size to be added by request. Naturally, this judgment may be made with a program or the like making such a request, ~~while~~ Alternatively, there may be employed a ~~constitution~~ configuration in which the interface unit 101 is imparted with a judgment function, and for example, when the interface unit 101 receives a request to add a partition having a size of 5, a partition having a size of 8 as a minimum additional size sufficient for satisfying the request is added. For simplicity, this embodiment will be explained on the assumption that the size 2 to the n-th power times as large is requested of this system.

[0040] In this embodiment, ~~further,~~ a position where the partition can be located when created, that is, the position that can be set as a starting position of the partition, is limited to a position (sector number) where the partition size is aligned.

[0041] Specifically, if a requested partition has a size of

256 (2^8) sectors, the location where this partition can be located is limited to regions with sector numbers 0, 256, 512, 768... (m times 256) as starting positions, where the partition size is aligned. Further, when the size of a partition is, for example, 1 as 2 to 0-th power, the partition can be positioned at any sector number.

[0042] ~~On the premise of the above regulations~~Based on the foregoing, the interface unit 101 requests the partition management execution unit 102 to execute the addition of the partition upon receipt of a request to add the partition and the size of the partition to be added. The processing of the partition management execution unit 102 having received this request will be explained with reference to the flowchart of Fig. 4.

[0043] First, the partition management execution unit 102 refers to the partition management table 103, and checks whether or not an empty undefined region equal to the requested size exists (S101).

[0044] ~~As a result, when the~~If an empty region exists, the partition management execution unit 102 creates a partition at the requested size in the empty region (S106), and reports the creation of the partition to a requester through the interface unit 101. Further, the partition management execution unit 102 updates the partition management table 103 on the basis of the location and the size of the created partition, and creates a header portion of the partition of

the hard disk 110.

[0045] Since the empty undefined region having the requested size is always aligned with the requested size by processing to be described later, it is possible to dispose a partition having the concerned size in this empty region.

[0046] When no empty region exists, ~~as a result of is~~ determined by checking whether or not there is an empty undefined region having the requested size, the partition management execution unit 102 checks whether or not there is an empty undefined region having a size 2m times (2, 4, 6, 8...) the requested size (S102).

[0047] ~~As a result, when the~~ If an empty undefined region having the size 2m times the requested size exists, the partition management execution unit 102 continues to divide the empty undefined region into halves ~~till~~ until the empty undefined region has the requested size, and creates new regions (S103). And when a region having the requested size is created, the partition management execution unit 102 creates a partition in the region (S106). Meanwhile, the partition management execution unit 102 updates the partition management table 103 with other newly created region as empty undefined regions, and creates a header portion.

[0048] ~~Fig. 5 is a view~~ Figs. 5A-5D are views for explaining one example of the above processing. ~~This drawing shows~~ These drawings show an example of the case where the creation

of a partition having a size 2 is requested in a state where a sector number 8 has an empty undefined region having a size 8 (Fig. 5A).

[0049] Since the empty undefined region having the size 8, which starts from the sector number 8, is 4 times as large as the requested size 2, this region meets the condition of $2m$ times. First, this region is divided into halves. Then, two empty undefined regions having a size 4 each are created (Fig. 5B). ~~And, an~~ An empty undefined region having a lower sector number is further divided into halves. Then, two empty undefined regions having a size 2 each are created (Fig. 5C).

[0050] Since these empty undefined regions have a size equal to the requested size, the partition is created in an empty undefined region having the size 2 and having a lower sector number. ~~And, the~~ The partition management execution unit 102 updates the partition management table 103 with other newly created regions as empty undefined regions, and creates and updates a header (Fig. 5D).

[0051] When there is not an empty undefined region having a size $2m$ times as large as the requested size, as a result of is determined by checking whether or not there is an empty undefined region $2m$ times as large, the partition management execution unit 102 checks whether or not the final undefined region is aligned with the requested size (S104).

[0052] As a result, when the final undefined region is

aligned with the requested size, the partition management execution unit 102 creates the partition at the requested size from a starting position of the final undefined region (S106). ~~And, the~~ The partition management execution unit 102 sets a remaining region as a final undefined region.

[0053] When the final undefined region is not aligned with the requested size, the partition management execution unit 102 creates an empty undefined region to a position where alignment is made (S105), and creates the partition at the requested size therein (S106).

[0054] Fig. 6 is a view for explaining one example of the above processing. This example is an example of the case where a partition with a size 1024 is requested when the final undefined region starts from a sector number 512 (Fig. 6A). Since the size 1024 is not aligned with the sector number 512 as a starting position of the final defined region, the partition management execution unit 102 sets a region from the sector number 512 to the sector number 1023 as an empty undefined region, and creates the partition with the size 1024 at the sector number 1024. Furthermore, the partition management execution unit 102 sets, as a final undefined region, a region of a sector number 2048 and thereafter, which region is a remaining region (Fig. 6B). ~~And, the~~ The partition management execution unit 102 updates the partition management table 103, and creates and updates a header portion.

[0055] The partitions are created as described above, so that the partitions can be disposed in the positions aligned with the requested sizes.

[0056] The processing of deleting a partition will be explained with reference to a flowchart of Fig. 7.

[0057] The interface unit 101 of the partition management system 100 requests that the partition management execution unit 102 ~~to execute deletion of~~ delete a partition upon receipt of a deletion request designating a specified partition from an operator, the program under execution, or the like.

[0058] The method of designating a partition to be deleted can be a method of designating an identifier such as a starting sector number, a partition number, or the like, of the partition. Naturally, the present invention is not limited to such a method, and the partition to be deleted can be specified by information to which the partition management execution unit 102 can refer and which permits designation of the partition to be deleted.

[0059] First, the partition management execution unit 102 deletes the designated partition, and sets a region thereof as an undefined region (S201).

[0060] Then, the partition management execution unit 102 judges whether or not the deleted partition is the last one of the defined partitions, that is, whether or not a region immediately after the deleted partition has been the final

undefined region (S202).

[0061] ~~As a result, when~~ When the deleted partition has been the last partition, the partition management execution unit 102 incorporates the undefined region caused by such deletion into the final undefined region (S203). Further, the partition management execution unit 102 judges whether or not a region immediately before the deleted partition has been an empty undefined region (S204), and when the region is ~~the~~ an empty undefined region, the partition management execution unit 102 also incorporates the region into the final undefined region (S205).

[0062] On the other hand, when the deleted partition is not the last partition, the partition management execution unit 102 judges whether or not a region immediately before the region that has been set as an undefined region is an empty undefined region (S206). ~~Then, when the~~ When that region is an empty undefined region, the partition management execution unit 102 judges whether or not the region is aligned when the two undefined regions are combined (S207), and when the region can be aligned, the two undefined regions are combined and set as one undefined region (S208).

[0063] Further, the partition management execution unit 102 judges whether or not a region immediately after the empty undefined region caused by the deletion or the empty undefined region caused by such combination is an empty undefined region (S209). Then, when the region is an empty

undefined region, the partition management execution unit 102 judges whether or not the region can be aligned when the two undefined regions are combined (S210), and when the region can be aligned, the two undefined regions are combined and set as one undefined region (S211).

[0064] Then, the partition management execution unit 102 reports the deletion of the partition to the requester through the interface unit 101. Further, the partition management execution unit 102 updates the header portion of each partition and the partition management table 103, and terminates the processing of deleting the partition.

[0065] ~~Fig. 8 is a view~~ Figs. 8A-8G are views for explaining ~~one example~~ examples of the above processing. When a partition D is deleted in Fig. 8A, a region immediately after the region from which the partition D is deleted is the final undefined region, so that the region from which the partition D has been deleted is added to the final undefined region as shown in Fig. 8B (S203).

[0066] When a partition D is deleted in Fig. 8C, the region from which the partition D is deleted is added to the final undefined region. In this case, a region immediately before that region is an undefined region F, so that the undefined region F is also added to the final undefined region as shown in Fig. 8D (S205).

[0067] When a partition D is deleted in Fig. 8E, if the total size of a region from which the partition D is deleted and

an undefined region F immediately before that region can be aligned, these two partitions are combined to be set as one undefined region G as shown in Fig. 8F (S208). On the other hand, if the total size ~~is~~ cannot be aligned, two undefined regions, ~~that are namely,~~ an undefined region D (as a result of deleting the partition D) and an undefined region F are generated as shown in Fig. 8G.

[0068] ~~When the~~ With a partition size ~~is~~ limited to 2 to the n-th power, ~~simulation results about~~ simulations of utilization efficiencies of the hard disk ~~will be shown have~~ been conducted with regard to: a case (A), where the partition is disposed only at the position aligned with the partition size; and a case (B), where the partition is disposed at an arbitrary position below.

[0069] ~~As a simulation~~ The above simulations were conducted using the following method: 50 partitions having eight sizes of 8 megabytes, 16 megabytes, 32 megabytes, 64 megabytes, 128 megabytes, 256 megabytes, 512 megabytes and 1 gigabyte ~~are were~~ pre-created on the hard disk at random ~~processings; processes~~ (1) to (3), shown below, ~~are were~~ iterated 1000 times while changing types of random numbers; and then, states of the hard disk ~~are were~~ compared.

[0070] (1) Deleting one partition by use of random numbers;

[0071] (2) Selecting any one of the above-described eight sizes by use of the random numbers, and adding a partition of the size; and

[0072] (3) ~~Iterating the processings of the above processes~~
(1) and (2) 100 times.

[0073] As a result of the simulations, the total ~~numbers~~
number of sectors to the last partition (total number of
sectors) and percentages of empty regions included in the
total sectors to the last partition (empty/total) were
determined as shown in Table 1 below.

[Table 1]

	A	B
Total Number of Sectors	35,287,040	33,820,672
Empty/Total	25.95%	21.78%

[0074] The above simulation results show that the present
invention improves the utilization efficiency of the hard
disk.

[0075] As described above, the utilization efficiency of
the storage device can be improved according to the present
invention.

[0076] Although the invention herein has been described
with reference to particular embodiments, it is to be
understood that these embodiments are merely illustrative
of the principles and applications of the present invention.
It is therefore to be understood that numerous modifications
may be made to the illustrative embodiments and that other
arrangements may be devised without departing from the
spirit and scope of the present invention as defined by the


appended claims.

ABSTRACT

A size of a partition to be created on a storage device is limited to a size of m to n -th power, where m and n are natural numbers. In creation of the partition, a partition management execution unit—102 is set to dispose the partition from a sector aligned with a size of the partition itself.——Thus, thereby improving the utilization efficiency of the storage device can be improved.

343862_1.DOC

FIG. 4



Approved
4/16/04
PMV